

# OL40U3PB



Products Low Voltage Products and Systems Switches Cam Switches

## General Information

<b>Extended Product Type:</b>	OL40U3PB
<b>Product ID:</b>	1SCA022761R1110
<b>EAN:</b>	4034656525781
<b>Catalog Description:</b>	OL40U3PB Cam switch
<b>Long Description:</b>	With 0-position, step angle 60°, door mounted, snap-on mounted handle

## Additional Information

<b>Ampere Rating UL/CSA:</b>	600 V AC 40 A
<b>Color:</b>	Black
<b>Conventional Free-air Thermal Current (I<sub>th</sub>):</b>	q = 40 °C 45 A
<b>Country of Origin:</b>	Germany (DE)
<b>Customs Tariff Number:</b>	85365080
<b>Data Sheet, Technical Information:</b>	1SCC302003C0201
<b>Declaration of Conformity - CE:</b>	1SCC302001D0204
<b>EAN:</b>	4034656525781
<b>ETIM 5:</b>	EC002611 - Control switch
<b>ETIM 6:</b>	EC002611 - Control switch
<b>Enclosure Type:</b>	Not enclosed
<b>Function:</b>	U3
<b>Handle Type:</b>	Basic handle
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SCC302004M0203
<b>Invoice Description:</b>	OL40U3PB Cam switch
<b>Minimum Order Quantity:</b>	1 piece
<b>Mounting Type:</b>	Snap-on door mounting
<b>Number of Contacts:</b>	6
<b>Number of Poles:</b>	3
<b>Object Classification Code:</b>	Q
<b>Order Multiple:</b>	1 piece
<b>Package Level 1 EAN:</b>	4034656525781
<b>Package Level 1 Gross Weight:</b>	0.33 kg
<b>Package Level 1 Height:</b>	110 mm
<b>Package Level 1 Length:</b>	250 mm
<b>Package Level 1 Units:</b>	10 piece
<b>Package Level 1 Width:</b>	100 mm
<b>Pollution Degree:</b>	3
<b>Power Loss:</b>	2.9 W
<b>Price Category:</b>	Standard
<b>Product Main Type:</b>	OL40
<b>Product Name:</b>	Cam switch
<b>Product Net Depth:</b>	111 mm
<b>Product Net Height:</b>	56 mm
<b>Product Net Weight:</b>	0.33 kg

<b>Product Net Width:</b>	51 mm
<b>Rated Continuous Thermal Current:</b>	45 A
<b>Rated Impulse Withstand Voltage (<math>U_{imp}</math>):</b>	6 kV
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	690 V
<b>Rated Operational Current AC-22A (<math>I_e</math>):</b>	(500 V) 40 A (690 V) 40 A
<b>Rated Operational Power AC-23A (<math>P_e</math>):</b>	(500 V) 15 kW (690 V) 15 kW (415 V) 15 kW (220 ... 240 V) 7.5 kW
<b>Rated Operational Voltage:</b>	690 V
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	for 3 s 0.36 kiloampere rms
<b>RoHS Information:</b>	1SCC302004D0201
<b>Selling Unit of Measure:</b>	piece
<b>Short Description:</b>	3-pole change-over cam switch with 0-position
<b>Special Functions:</b>	Change-over switch: With 0-position: 12 o'clock, step angle 60°, front plate 1-0-2
<b>Terminal Type:</b>	Screw Terminals

