

# CR-P024AC2



Products Low Voltage Products and Systems Control Products Electronic Relays and Controls  
Interface Relays and Optocouplers

## General Information

<b>Extended Product Type:</b>	CR-P024AC2
<b>Product ID:</b>	1SVR405601R0000
<b>EAN:</b>	4013614498220
<b>Catalog Description:</b>	CR-P024AC2 Pluggable interface relay 2c/o, A1-A2=24VAC, 250V/8A
<b>Long Description:</b>	The CR-P024AC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 24 V AC rated control supply voltage and has a 2 c/o (SPDT) output with c contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

## Additional Information

<b>CCC Certificate:</b>	CCC_2007010303228779
<b>CSA Certificate:</b>	CSA_1587291
<b>Contact Material:</b>	silver-nickel alloy (AgNi)
<b>Country of Origin:</b>	Poland (PL)
<b>Customs Tariff Number:</b>	85364900
<b>Data Sheet, Technical Information:</b>	2CDC117001D0203
<b>Declaration of Conformity - CE:</b>	No declaration needed
<b>Degree of Protection:</b>	IP67
<b>E-nummer:</b>	4005307
<b>EAC Certificate:</b>	EAC_RU_C-PL.ME77.B.01873
<b>EAN:</b>	4013614498220
<b>EPLAN Catalog Tree:</b>	Electrical engineering / Relays, contactors / General
<b>ETIM 4:</b>	EC001437 - Switching relay
<b>ETIM 5:</b>	EC001437 - Switching relay
<b>ETIM 6:</b>	EC001437 - Switching relay
<b>Environmental Information:</b>	1SAA981009-2401
<b>Function:</b>	Pluggable pcb interface relay CR-P
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SVC405600M9000
<b>Integrated Free-Wheeling Diode:</b>	No
<b>Interface Relay Type:</b>	Pluggable Circuit Board (PCB)
<b>Invoice Description:</b>	CR-P024AC2 Pluggable interface relay 2c/o, A1-A2=24VAC, 250V/8A
<b>Manual Operation:</b>	No
<b>Maximum Switching Voltage:</b>	250 V
<b>Minimum Order Quantity:</b>	10 piece
<b>Number of Contacts CO:</b>	2
<b>Number of Contacts NC:</b>	0
<b>Number of Contacts NO:</b>	0
<b>Number of LEDs:</b>	0
<b>Object Classification Code:</b>	K
<b>Output:</b>	2 c/o (SPDT) contacts
<b>Output Current:</b>	8 A
<b>Output Signal:</b>	250 V / 8 A
<b>Package Level 1 EAN:</b>	4013614372995

Package Level 1 Gross Weight:	0.157 kg
Package Level 1 Height:	28 mm
Package Level 1 Length:	17 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	332 mm
Power Loss:	Approximately 2 W
Product Main Type:	CR-P
Product Name:	Pluggable Interface Relay
Product Net Depth:	29 mm
Product Net Height:	15.7 mm
Product Net Weight:	0.014 kg
Product Net Width:	12.7 mm
RMRS Certificate:	RMRS_1740019250
Rated Control Supply Voltage (U <sub>s</sub> ):	24 V AC
Rated Operational Current (I <sub>e</sub> ):	8 A
Regulatory Compliance Mark (RCM):	No
RoHS Date:	1146
RoHS Information:	1SVD981001-4400
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CR-P024AC2 Pluggable interface relay
Standards:	IEC/EN 61810-1
Sub-Function:	Relay w/o built in LED
UNSPSC:	39121500
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40019129
cUR Certificate:	cUR_E244330
eClass:	7.0 27371601

