

General Information

Extended Product Type:	CT-MKE
Product ID:	1SVR550019R0000
EAN:	4013614346149
Catalog Description:	CT-MKE Time relay, solid-state, multif. 1n/o, 0.1-10s/3-300s, 24-240VAC/DC
Long Description:	The CT-MKE is a multifunction electronic time relay from the CT-E timer range. It provides 4 timing functions with 2 time ranges from 0.1 s to 300 s. This time relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a solid-state output.

Additional Information

Analog Inputs:	0
Country of Origin:	Germany (DE)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC111146D0201
Declaration of Conformity - CE:	1SVD981002-0000
EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
EAN:	4013614346149
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
ETIM 6:	EC001439 - Timer relay
Environmental Information:	1SAA981011-2402
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SVC550000M9000
Invoice Description:	CT-MKE Time relay, solid-state, multif. 1n/o, 0.1-10s/3-300s, 24-240VAC/DC
Minimum Order Quantity:	1 piece
Mounting Position:	Any
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Digital Inputs:	0
Object Classification Code:	K
Output:	solid-state output
Package Level 1 EAN:	4013614346149
Package Level 1 Gross Weight:	0.07 kg
Package Level 1 Height:	83.1 mm
Package Level 1 Length:	24.6 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	84.2 mm
Power Loss:	Approximately 2 W
Product Main Type:	CT-MKE
Product Name:	Time Relay
Product Net Depth:	78.5 mm
Product Net Height:	78 mm
Product Net Weight:	0.059 kg
Product Net Width:	22.5 mm
EMPS Certificate:	EMPS 1710021250

RWRS Certificate:	RWRS_1740021230
Rated Control Supply Voltage (U_s):	24 ... 240 V AC/DC
Regulatory Compliance Mark (RCM):	Yes
RoHS Date:	1146
RoHS Information:	1SVD981001-4400
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CT-MKE Time relay, solid-state, multif.
Standards:	IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14
Terminal Type:	Screw Terminals
Time Range:	0.1-10 s, 3-300 s
Timer Relay Type:	ON-Delay Impulse ON Flasher Starting with ON Flasher Starting with OFF
UL Certificate:	UL508_E140448
UNSPSC:	39121500
cUL Certificate:	cUL508_E140448
eClass:	7.0 27371790
DNV GL Certificate:	DNV_GL_TAA00000F2