

General Information

Extended Product Type:	CM-PVE
Product ID:	1SVR550871R9500
EAN:	4013614348112
Catalog Description:	CM-PVE Phase monitoring relay 1n/o, L1,2,3=320-460VAC
Long Description:	Phase monitoring relay CM-PVE, width 22.5mm, monitoring of single- or three phase over- and undervoltage, phase loss, measuring range L1-L2-L3=320-460VAC, powered by measuring circuit, 1 n/o (closed circuit principle)

Additional Information

CB Certificate:	CB_DK-8880
CCC Certificate:	CCC_2013010303605960
Country of Origin:	Bulgaria (BG)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC112190D0201
Declaration of Conformity - CE:	1SVD981025-0000
EAC Certificate:	EAC_RU_C-BG.ME77.B.00507
EAN:	4013614348112
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
ETIM 4:	EC001441 - Phase monitoring relay
ETIM 5:	EC001441 - Phase monitoring relay
ETIM 6:	EC001441 - Phase monitoring relay
Environmental Information:	1SAA981003-2403
Function:	Phase failure detection Over- and undervoltage monitoring
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SVC550510M0001
Invoice Description:	CM-PVE Phase monitoring relay 1n/o, L1,2,3=320-460VAC
Measurement Threshold:	Fixed
Measuring Range:	(L-L) 320 ... 460 V AC
Minimum Order Quantity:	1 piece
Object Classification Code:	B
Output:	1 n/o contact
Package Level 1 EAN:	4013614348112
Package Level 1 Gross Weight:	0.078 kg
Package Level 1 Height:	83 mm
Package Level 1 Length:	25 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	24 mm
Power Loss:	Approximately 2 W
Product Main Type:	CM-PVE
Product Name:	Three-Phase Monitoring Relay
Product Net Depth:	78.5 mm
Product Net Height:	78 mm
Product Net Weight:	0.066 kg
Product Net Width:	22.5 mm

PRODUCT REFERENCE:	22.0 11111
RMRS Certificate:	RMRS_1740020250
Rated Control Supply Voltage (U _s):	(L-L) 320 ... 460 V AC
Rated Frequency (f):	Supply Circuit 50/60 Hz
Regulatory Compliance Mark (RCM):	Yes
RoHS Date:	1146
RoHS Information:	1SVD981001-4400
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CM-PVE Phase monitoring relay
Standards:	EN 50178 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508 CAN/CSA C22.2 No.14
Sub-Function:	Phase loss
Sub-Function 2:	02 Over- and undervoltage (fixed)
Sub-Function 3:	Over- and undervoltage (fixed)
Terminal Type:	Screw Terminals
Time Range:	500 ms start-up delay 500 ms tripping delay
UL Certificate:	UL508_E140448
UNSPSC:	39121500
cUL Certificate:	cUL508_E140448
eClass:	7.0 27371803

