

Products Low Voltage Products and Systems Industrial Plugs and Sockets Tough & Safe Plugs

### General Information

<b>Extended Product Type:</b>	363P6
<b>Product ID:</b>	2CMA166752R1000
<b>EAN:</b>	7392696667524
<b>Catalog Description:</b>	Ind. P&S#363P6
<b>Long Description:</b>	Plug, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

### Additional Information

<b>Additional Information:</b>	3P+E
<b>Cable Cross-Section:</b>	4 ... 16 mm <sup>2</sup>
<b>Cable Entry Position:</b>	Cable entry, membrane
<b>Color:</b>	Red
<b>Connection Type:</b>	Screw clamp
<b>Country of Origin:</b>	Czech Republic (CZ)
<b>Customs Tariff Number:</b>	85366990
<b>Data Sheet, Technical Information:</b>	2CMC700014C0008
<b>Declaration:</b>	2CMC700005D0001
<b>Declaration of Conformity - CE:</b>	2CMC700005D0001
<b>Degree of Protection:</b>	IP44
<b>E-nummer:</b>	2416226
<b>EAN:</b>	7392696667524
<b>ETIM 4:</b>	EC000140 - CEE plug
<b>ETIM 5:</b>	EC000140 - CEE plug
<b>ETIM 6:</b>	EC000140 - CEE plug
<b>Enclosure Material:</b>	Thermoplastic polyester (PBT)
<b>Environmental Information:</b>	2CMC700001D0002
<b>Frequency (f):</b>	50 Hz
<b>Function:</b>	Plug
<b>Gross Weight:</b>	0.72 kg
<b>Housing Material:</b>	Thermoplastic (PBT)
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Instructions and Manuals:</b>	2CMC700002D0001
<b>Invoice Description:</b>	Ind. P&S#363P6
<b>Minimum Order Quantity:</b>	1 piece
<b>Number of Poles:</b>	4
<b>Object Classification Code:</b>	2CMT005069
<b>Package Level 1 EAN:</b>	7392696667524
<b>Package Level 1 Gross Weight:</b>	0.72 kg
<b>Package Level 1 Height:</b>	230 mm
<b>Package Level 1 Length:</b>	114 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	114 mm
<b>Product Main Type:</b>	TP
<b>Product Name:</b>	Industrial Plug
<b>Product Net Depth:</b>	215 mm

<b>Product Net Height:</b>	103 mm
<b>Product Net Length:</b>	215 mm
<b>Product Net Weight:</b>	0.64 kg
<b>Product Net Width:</b>	103 mm
<b>Protection Type:</b>	Splashproof
<b>Rated Current (I<sub>n</sub>):</b>	63 A
<b>Rated Voltage (U<sub>r</sub>):</b>	380 ... 415 V
<b>RoHS Date:</b>	L23
<b>RoHS Information:</b>	2CMC700057D0001
<b>Selling Unit of Measure:</b>	piece
<b>Short Description:</b>	Plug, 6h, 63A, IP44, 3P+E
<b>Size:</b>	215X103X103
<b>Standards:</b>	IEC 60309-1 IEC 60309-2
<b>Suitable For:</b>	Plugs
<b>Suitable for Product Class:</b>	Industrial Plugs and Sockets
<b>UNSPSC:</b>	39120000
<b>Clock Position Of Grounding Contact:</b>	6 hour
<b>RAL Number:</b>	RAL 7001 - Silver Grey

