

General Information

Extended Product Type:	263C6
Product ID:	2CMA166840R1000
EAN:	7392696668408
Catalog Description:	Ind. P&S#263C6
Long Description:	Connector, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 2-poles+earth , frequency 50-60 Hz, color code Blue

Additional Information

Additional Information:	2P+E
Cable Cross-Section:	4 ... 16 mm ²
Cable Entry Position:	Cable entry, membrane
Color:	Blue
Connection Type:	Screw clamp
Country of Origin:	Czech Republic (CZ)
Customs Tariff Number:	85366990
Data Sheet, Technical Information:	2CMC700014C0008
Declaration:	2CMC700005D0001
Declaration of Conformity - CE:	2CMC700005D0001
Degree of Protection:	IP44
E-nummer:	2416345
EAN:	7392696668408
ETIM 4:	EC001321 - CEE socket outlet
ETIM 5:	EC001321 - CEE socket outlet
ETIM 6:	EC001320 - CEE coupling
Enclosure Material:	Thermoplastic polyester (PBT)
Environmental Information:	2CMC700001D0002
Frequency (f):	60 Hz
Function:	Connector
Gross Weight:	0.88 kg
Housing Material:	Plastic (PA)
IIT Publishing Status:	Level 0 - Information enabled
Instructions and Manuals:	2CMC700002D0001
Invoice Description:	Ind. P&S#263C6
Minimum Order Quantity:	1 piece
Number of Poles:	3
Object Classification Code:	2CMT005069
Package Level 1 EAN:	7392696668408
Package Level 1 Gross Weight:	0.88 kg
Package Level 1 Height:	230 mm
Package Level 1 Length:	114 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	114 mm
Product Main Type:	TC
Product Name:	Industrial Connector
Product Net Depth:	224 mm

Product Net Height:	112 mm
Product Net Length:	224 mm
Product Net Weight:	0.8 kg
Product Net Width:	98 mm
Protection Type:	Splashproof
Rated Current (I_n):	63 A
Rated Voltage (U_r):	200 ... 250 V
RoHS Date:	L23
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1614200
Selling Unit of Measure:	piece
Short Description:	Connector, 6h, 63A, IP44, 2P+E
Size:	224X98X112
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Connectors
Suitable for Product Class:	Industrial Plugs and Sockets
UNSPSC:	39120000
Clock Position Of Grounding Contact:	6 hour
RAL Number:	RAL 7001 - Silver Grey

