

## General Information

|                               |   |
|-------------------------------|---|
| <b>Extended Product Type:</b> | 363C6   |
| <b>Product ID:</b>            | 2CMA166850R1000   |
| <b>EAN:</b>                   | 7392696668507   |
| <b>Catalog Description:</b>   | Ind. P&S#363C6  |
| <b>Long Description:</b>      | Connector, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+earth , frequency 50-60 Hz, color code Red |

## Additional Information

|   |                               |
|---|-------------------------------|
| <b>Additional Information:</b>            | 3P+E                          |
| <b>Cable Cross-Section:</b>               | 4 ... 16 mm <sup>2</sup>      |
| <b>Cable Entry Position:</b>              | Cable entry, membrane         |
| <b>Color:</b>                             | Red                           |
| <b>Connection Type:</b>                   | Screw clamp                   |
| <b>Country of Origin:</b>                 | Czech Republic (CZ)           |
| <b>Customs Tariff Number:</b>             | 85366990                      |
| <b>Data Sheet, Technical Information:</b> | 2CMC700014C0008               |
| <b>Declaration:</b>                       | 2CMC700005D0001               |
| <b>Declaration of Conformity - CE:</b>    | 2CMC700005D0001               |
| <b>Degree of Protection:</b>              | acc. to IEC 60529 IP44        |
| <b>E-nummer:</b>                          | 2416350                       |
| <b>EAN:</b>                               | 7392696668507                 |
| <b>ETIM 4:</b>                            | EC001321 - CEE socket outlet  |
| <b>ETIM 5:</b>                            | EC001321 - CEE socket outlet  |
| <b>ETIM 6:</b>                            | EC001320 - CEE coupling       |
| <b>Enclosure Material:</b>                | Thermoplastic polyester (PBT) |
| <b>Environmental Information:</b>         | 2CMC700001D0002               |
| <b>Frequency (f):</b>                     | 50 Hz                         |
| <b>Function:</b>                          | Connector                     |
| <b>Gross Weight:</b>                      | 0.88 kg                       |
| <b>Housing Material:</b>                  | Plastic (PA)                  |
| <b>IIT Publishing Status:</b>             | Level 0 - Information enabled |
| <b>Instructions and Manuals:</b>          | 2CMC700002D0001               |
| <b>Invoice Description:</b>               | Ind. P&S#363C6                |
| <b>Minimum Order Quantity:</b>            | 1 piece                       |
| <b>Number of Poles:</b>                   | 4                             |
| <b>Object Classification Code:</b>        | 2CMT005069                    |
| <b>Package Level 1 EAN:</b>               | 7392696668507                 |
| <b>Package Level 1 Gross Weight:</b>      | 0.88 kg                       |
| <b>Package Level 1 Height:</b>            | 230 mm                        |
| <b>Package Level 1 Length:</b>            | 114 mm                        |
| <b>Package Level 1 Units:</b>             | 1 piece                       |
| <b>Package Level 1 Width:</b>             | 114 mm                        |
| <b>Product Main Type:</b>                 | TC                            |
| <b>Product Name:</b>                      | Industrial Connector          |
| <b>Product Net Depth:</b>                 | 224 mm                        |

|   |                                |
|---|--------------------------------|
| <b>Product Net Height:</b>                  | 112 mm                         |
| <b>Product Net Length:</b>                  | 224 mm                         |
| <b>Product Net Weight:</b>                  | 0.8 kg                         |
| <b>Product Net Width:</b>                   | 98 mm                          |
| <b>Protection Type:</b>                     | Splashproof                    |
| <b>Rated Current (I<sub>n</sub>):</b>       | 63 A                           |
| <b>Rated Voltage (U<sub>r</sub>):</b>       | 380 ... 415 V                  |
| <b>RoHS Date:</b>                           | L23                            |
| <b>RoHS Information:</b>                    | 2CMC700057D0001                |
| <b>SEMKO Certificate:</b>                   | 1614200                        |
| <b>Selling Unit of Measure:</b>             | piece                          |
| <b>Short Description:</b>                   | Connector, 6h, 63A, IP44, 3P+E |
| <b>Size:</b>                                | 224X98X112                     |
| <b>Standards:</b>                           | IEC 60309-1<br>IEC 60309-2     |
| <b>Suitable For:</b>                        | Connectors                     |
| <b>Suitable for Product Class:</b>          | Industrial Plugs and Sockets   |
| <b>UNSPSC:</b>                              | 39120000                       |
| <b>Clock Position Of Grounding Contact:</b> | 6 hour                         |
| <b>RAL Number:</b>                          | RAL 7001 - Silver Grey         |

