

General Information

Extended Product Type:	232RS6
Product ID:	2CMA193122R1000
EAN:	7392696931229
Catalog Description:	Surface socket-outlet, 6h, 32A, IP44, 2P+E
Long Description:	Surface socket-outlet, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue

Additional Information

Additional Information:	2P+E
Cable Cross-Section:	2.5 ... 10 mm ²
Cable Diameter:	22 mm
Cable Entry Position:	Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry.
Color:	Blue
Connection Type:	Screw clamp
Country of Origin:	Czech Republic (CZ)
Customs Tariff Number:	85366990
Data Sheet, Technical Information:	2CMC700014C0008
Declaration:	2CMC700005D0001
Declaration of Conformity - CE:	2CMC700005D0001
Degree of Protection:	IP44
E-number:	2416491
EAN:	7392696931229
ETIM 4:	EC001321 - CEE socket outlet
ETIM 5:	EC001321 - CEE socket outlet
ETIM 6:	EC001321 - CEE socket outlet
Enclosure Material:	Thermoplastic
Environmental Information:	2CMC700001D0002
Frequency (f):	60 Hz
Function:	Surface socket outlet
Gross Weight:	0.331 kg
Housing Material:	Plastic (PA)
IIT Publishing Status:	Level 0 - Information enabled
Instructions and Manuals:	2CMC700002D0001
Invoice Description:	Ind. P&S#232RS6
Minimum Order Quantity:	10 piece
Number of Poles:	3
Object Classification Code:	2CMT005069
Package Level 1 EAN:	7392696661225
Package Level 1 Gross Weight:	3 kg
Package Level 1 Height:	428 mm
Package Level 1 Length:	175 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	188 mm
Product Main Type:	ERS

Product Name:	Wall mounted socket
Product Net Depth:	163 mm
Product Net Height:	118 mm
Product Net Length:	163 mm
Product Net Weight:	0.3 kg
Product Net Width:	85 mm
Protection Type:	Splashproof
Rated Current (I_n):	32 A
Rated Voltage (U_r):	200 ... 250 V
RoHS Date:	L23
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1613211
Selling Unit of Measure:	piece
Short Description:	Surface socket-outlet, 6h, 32A, IP44, 2P+E
Size:	118X85X163
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Surface Socket Outlets
Suitable for Product Class:	Industrial Plugs and Sockets
UNSPSC:	39120000
Clock Position Of Grounding Contact:	6 hour
RAL Number:	RAL 7001 - Silver Grey

