

General Information

Extended Product Type:	316-P9
Product ID:	2CMA193508R1000
EAN:	7392696935081
Catalog Description:	Plug, 9h, 16A, IP44, 3P+E
Long Description:	Plug, earthing sleeve position 9h, rated current 16A, IP44 splashproof, 3-poles+earth, 50 - 60 Hertz, color code blue

Additional Information

Additional Information:	3P+E
Cable Cross-Section:	1.0 ... 2.5 mm ²
Cable Diameter:	17 mm
Cable Entry Position:	Cable entry, compression gland
Color:	Blue
Connection Type:	Screw clamp
Country of Origin:	Czech Republic (CZ)
Customs Tariff Number:	85366990
Data Sheet, Technical Information:	2CMC700014C0008
Declaration:	2CMC700005D0001
Declaration of Conformity - CE:	2CMC700005D0001
Degree of Protection:	IP44
E-nummer:	2416167
EAN:	7392696935081
ETIM 4:	EC000140 - CEE plug
ETIM 5:	EC000140 - CEE plug
ETIM 6:	EC000140 - CEE plug
Enclosure Material:	Polyamide
Environmental Information:	2CMC700001D0002
Frequency (f):	60 Hz
Function:	Plug
Gross Weight:	1.58 kg
Housing Material:	Plastic (PA)
IIT Publishing Status:	Level 0 - Information enabled
Instructions and Manuals:	2CMC700058M0001
Invoice Description:	Ind. P&S#316-P9
Minimum Order Quantity:	10 piece
Number of Poles:	4
Object Classification Code:	2CMT005069
Package Level 1 EAN:	7392696650083
Package Level 1 Gross Weight:	1.58 kg
Package Level 1 Height:	345 mm
Package Level 1 Length:	158 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	138 mm
Product Main Type:	EP
Product Name:	Industrial Plug

Product Net Depth:	142 mm
Product Net Height:	73 mm
Product Net Length:	142 mm
Product Net Weight:	0.158 kg
Product Net Width:	73 mm
Protection Type:	Splashproof
Rated Current (I_n):	16 A
Rated Voltage (U_r):	200 ... 250 V
Replacement Product ID (NEW):	2CMA101958R1000
RoHS Date:	L23
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1617364
Selling Unit of Measure:	piece
Short Description:	Plug, 9h, 16A, IP44, 3P+E
Size:	73X142X73
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Plugs
Suitable for Product Class:	Industrial Plugs and Sockets
UNSPSC:	39120000
Clock Position Of Grounding Contact:	9 hour
RAL Number:	RAL 7001 - Silver Grey

