

General Information

Extended Product Type:	332-C9
Product ID:	2CMA193530R1000
EAN:	7392696935302
Catalog Description:	Connector, 9h, 32A, IP44, 3P+E
Long Description:	Connector, earthing sleeve position 9h, rated current 32A, IP44 splashproof, 3-poles+earth, 50 - 60 Hertz, color code blue

Additional Information

Additional Information:	3P+E
Cable Cross-Section:	2.5 ... 6 mm ²
Cable Diameter:	22 mm
Cable Entry Position:	Cable entry, compression gland
Color:	Blue
Connection Type:	Screw clamp
Country of Origin:	Czech Republic (CZ)
Customs Tariff Number:	85366990
Data Sheet, Technical Information:	2CMC700014C0008
Declaration:	2CMC700005D0001
Declaration of Conformity - CE:	2CMC700005D0001
Degree of Protection:	IP44
E-nummer:	2416187
EAN:	7392696935302
ETIM 4:	EC001321 - CEE socket outlet
ETIM 5:	EC001321 - CEE socket outlet
ETIM 6:	EC001320 - CEE coupling
Enclosure Material:	Polyamide
Environmental Information:	2CMC700001D0002
Frequency (f):	60 Hz
Function:	Connector
Gross Weight:	2.73 kg
Housing Material:	Plastic (PA)
IIT Publishing Status:	Level 0 - Information enabled
Instructions and Manuals:	2CMC700058M0001
Invoice Description:	Ind. P&S#332-C9
Minimum Order Quantity:	10 piece
Number of Poles:	4
Object Classification Code:	2CMT005069
Package Level 1 EAN:	7392696650304
Package Level 1 Gross Weight:	2.73 kg
Package Level 1 Height:	378 mm
Package Level 1 Length:	182 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	154 mm
Product Main Type:	EC
Product Name:	Industrial Connector

Product Net Depth:	177 mm
Product Net Height:	96 mm
Product Net Length:	177 mm
Product Net Weight:	0.273 kg
Product Net Width:	96 mm
Protection Type:	Splashproof
Rated Current (I_n):	32 A
Rated Voltage (U_r):	200 ... 250 V
Replacement Product ID (NEW):	2CMA102042R1000
RoHS Date:	L23
RoHS Information:	2CMC700057D0001
SEMKO Certificate:	1615870
Selling Unit of Measure:	piece
Short Description:	Connector, 9h, 32A, IP44, 3P+E
Size:	96X177X96
Standards:	IEC 60309-1 IEC 60309-2
Suitable For:	Connectors
Suitable for Product Class:	Industrial Plugs and Sockets
UNSPSC:	39120000
Clock Position Of Grounding Contact:	9 hour
RAL Number:	RAL 7001 - Silver Grey