

# OVR T2 70-275S P



Products Low Voltage Products and Systems Modular DIN Rail Products Surge Protective Devices SPDs  
Surge Protective Devices SPD Class II

## General Information

<b>Extended Product Type:</b>	OVR T2 70-275S P
<b>Product ID:</b>	2CTB803851R1900
<b>EAN:</b>	3660308512819
<b>Catalog Description:</b>	OVR T2 70-275S P
<b>Long Description:</b>	B751281

## Additional Information

<b>Arrester Class:</b>	II
<b>Brand / Label:</b>	ABB
<b>Country of Origin:</b>	France (FR)
<b>Customs Tariff Number:</b>	85363090
<b>Data Sheet, Technical Information:</b>	2CTC432014D1701
<b>Declaration of Conformity - CE:</b>	2CTC436004G1701
<b>Discharge Current:</b>	Nominal 30 kA Maximum 70 kA Total 70 kA
<b>EAN:</b>	3660308512819
<b>ETIM 4:</b>	EC000941 - Surge protection device for power supply systems
<b>ETIM 5:</b>	EC000941 - Surge protection device for power supply systems
<b>ETIM 6:</b>	EC000941 - Surge protection device for power supply systems
<b>Instructions and Manuals:</b>	2CTC432004M1701
<b>Invoice Description:</b>	OVR T2 70-275S P
<b>Maximum Continuous Operating Voltage (U<sub>c</sub>):</b>	(L-PE) 275 V (L-L) 275 V (L-N) 275 V (N-PE) - V
<b>Mechanical Drawings:</b>	2CTC800021F0100.pdf 2CTC800021F0101.dxf 2CTC800021F0102.stp 2CTC800021F0103.igs
<b>Minimum Order Quantity:</b>	1 piece
<b>Nominal AC Voltage of the System (U<sub>0</sub>):</b>	230 / 400 V
<b>Number of Poles:</b>	1
<b>Number of Protected Poles:</b>	1
<b>Object Classification Code:</b>	141DCC
<b>Options Provided:</b>	Industry, commercial building
<b>Package Level 1 EAN:</b>	3660308512819
<b>Package Level 1 Gross Weight:</b>	150 g
<b>Package Level 1 Height:</b>	82 mm
<b>Package Level 1 Length:</b>	25 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	117 mm
<b>Preventive Maintenance Feature:</b>	No
<b>Product Main Type:</b>	T2
<b>Product Name:</b>	Surge Protective Device
<b>Product Net Depth:</b>	58 mm

<b>Product Net Height:</b>	88 mm
<b>Product Net Weight:</b>	125 g
<b>Product Net Width:</b>	17.8 mm
<b>Replacement Product ID (NEW):</b>	2CTB815708R1200
<b>Selling Unit of Measure:</b>	piece
<b>Short Circuit Withstand Icc:</b>	50 kA
<b>Short Description:</b>	OVR T2 70-275S P
<b>Short-Circuit Protective Devices:</b>	gG Type Fuses $\leq 50$ A gL Type Fuses $\leq 50$ A Curve B Breakers $\leq 50$ A Curve C Breakers $\leq 50$ A
<b>Standards:</b>	IEC 61643-1 / EN 61643-11
<b>Suitable For:</b>	To protect the systems against the transient overvoltage (lightning)
<b>Temporary Overvoltage Test Value (U<sub>T</sub>):</b>	337 V
<b>Type of Low Voltage Distribution System:</b>	TT TN-C TN-S
<b>UL Certificate:</b>	N
<b>Version:</b>	Plug-in
<b>Voltage Protection Level (U<sub>p</sub>):</b>	(L-N) - kV (N-PE) - kV (L-PE) 1.5 kV
<b>Voltage Rating DC:</b>	350 V

