

OVR T2 15-275 P



Products Low Voltage Products and Systems Modular DIN Rail Products Surge Protective Devices SPDs
Surge Protective Devices SPD Class II

General Information

| | |
|-------------------------------|-----------------|
| Extended Product Type: | OVR T2 15-275 P |
| Product ID: | 2CTB803851R2400 |
| EAN: | 3660308512840 |
| Catalog Description: | OVR T2 15-275 P |
| Long Description: | B751284 |

Additional Information

| | |
|--|--|
| Arrester Class: | II |
| Brand / Label: | ABB |
| Country of Origin: | France (FR) |
| Customs Tariff Number: | 85363090 |
| Data Sheet, Technical Information: | 2CTC432017D1701 |
| Declaration of Conformity - CE: | 2CTC436004G1701 |
| Discharge Current: | Nominal 5 kA Maximum 15 kA Total 15 kA |
| E-nummer: | 5273513 |
| EAN: | 3660308512840 |
| ETIM 4: | EC000941 - Surge protection device for power supply systems |
| ETIM 5: | EC000941 - Surge protection device for power supply systems |
| ETIM 6: | EC000941 - Surge protection device for power supply systems |
| Instructions and Manuals: | 2CTC432004M1701 |
| Invoice Description: | OVR T2 15-275 P |
| Maximum Continuous Operating Voltage (U_c): | (L-PE) 275 V (L-L) 275 V (L-N) 275 V (N-PE) - V |
| Mechanical Drawings: | 2CTC800021F0100.pdf 2CTC800021F0101.dxf 2CTC800021F0102.stp 2CTC800021F0103.igs |
| Minimum Order Quantity: | 1 piece |
| Nominal AC Voltage of the System (U_b): | 230 / 400 V |
| Number of Poles: | 1 |
| Number of Protected Poles: | 1 |
| Object Classification Code: | 141DCC |
| Package Level 1 EAN: | 3660308512840 |
| Package Level 1 Gross Weight: | 150 g |
| Package Level 1 Height: | 82 mm |
| Package Level 1 Length: | 25 mm |
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 117 mm |
| Preventive Maintenance Feature: | No |
| Product Main Type: | T2 |
| Product Name: | Surge Protective Device |
| Product Net Depth: | 58 mm |

| | |
|--|--|
| Product Net Height: | 88 mm |
| Product Net Weight: | 125 g |
| Product Net Width: | 17.8 mm |
| Replacement Product ID (NEW): | 2CTB803871R2400 |
| Selling Unit of Measure: | piece |
| Short Circuit Withstand Icc: | 50 kA |
| Short Description: | OVR T2 15-275 P |
| Short-Circuit Protective Devices: | gG Type Fuses ≤ 50 A gL Type Fuses ≤ 50 A Curve B Breakers ≤ 50 A Curve C Breakers ≤ 50 A |
| Standards: | IEC 61643-1 / EN 61643-11 |
| Suitable For: | To protect the systems against the transient overvoltage (lightning) |
| Temporary Overvoltage Test Value (U_T): | 337 V |
| Type of Low Voltage Distribution System: | TT TN-C TN-S |
| UL Certificate: | N |
| Version: | Plug-in |
| Voltage Protection Level (U_p): | (L-N) - kV (N-PE) - kV (L-PE) 1 kV |
| Voltage Rating DC: | 350 V |

